

# Leica iCON CC80

Rugged, lightweight controller for uncompromising site work



**icon**  
intelligent construction

Leica iCON CC80 controller is the world's thinnest and lightest fully rugged 7" Windows® tablet. It is built to enable easy, mobile work on site and increase worker productivity without compromise. Powered by Windows® 8.1 Pro and an Intel® Core i5 processor, Leica iCON CC80 features a long life, user replaceable battery and a daylight readable multi-touchscreen with high sensitivity for easy operation in all conditions. With the broad range of iCON software configuration options and flexible communication, the iCON CC80 is the ideal controller for site workers and foremen.

- Large 7" sunlight readable multi-touchscreen for convenient operation
- Microsoft Windows® 8.1 operating system, enables 3<sup>rd</sup> party applications as well
- Various wireless communication possibilities (Bluetooth®, WiFi and integrated 3G/4G multicarrier mobile broadband) for use with different sensors and internet access
- Fully rugged design for use in toughest conditions (MIL-STD-810G, IP65)
- Long life battery pack (up to 16 hours)
- Highly productive positioning work with Leica iCON site and Leica iCON build application software



# Leica iCON CC80

Rugged, mobile tablet PC



Technology	
<b>Processor &amp; Memory</b>	Intel® Core™ i5-4302Y vPro™ processor – 1.6 GHz with Intel® Turbo Boost up to 2.3 GHz – 3MB cache 4 GB SDRAM (DDR3L-1333 MHz)
<b>Data Storage</b>	128 GB solid state drive (SSD) with heater
<b>Operating System</b>	Microsoft Windows® 8.1 Pro 64-bit
<b>Screen</b>	7" widescreen, 1280x800 resolution, color TFT, 500 cd/m <sup>2</sup> (Nits), sunlight readable resistive capacitive touch display
<b>Keyboard &amp; Buttons</b>	Power button, volume button, auto rotate button, 1 programmable button, 10-point multi-touch, supports gloved touch and gestures and capacitive stylus pen; Stylus pen with integrated holder in rotating hand strap; On-screen QWERTY soft keyboard
<b>I/O Ports</b>	1x USB 3.0; 1x DC power input; Docking connector (24 pin); 1x audio out, mini-jack stereo; integrated microphone and speaker
Communication	
<b>Integrated Communication Modules</b>	Integrated 3G/4G multicarrier mobile broadband (depending on country variant) Intel® dual band wireless AC7260 Wi-Fi 802.11a/b/g/n/ac Bluetooth® v4.0 (Class 1) + EDR
<b>Integrated GPS</b>	L1 GPS integrated (depending on country variant)
<b>Integrated Camera</b>	2 MP front webcam with microphone, 5 MP rear camera with auto focus and LED light
<b>TPS 1-Man Mode Working Range<sup>1)</sup></b>	Typical 150m (490 ft); up to 200m (650 ft) with direct line of sight

<sup>1)</sup> Requires long-range Bluetooth handle on TPS and Standard Bluetooth on CC80. Range varies depending on local conditions.

Power Management	
<b>Batteries</b>	Li-Ion "Long life" battery pack: 7.2V, typical 7100 mAh, minimum 6800 mAh
<b>Power</b>	Input: 120-240 VAC, 50-60 Hz Output: 16 V DC, 3.75A
<b>Operating Time</b>	Long life battery pack: 16 h (benchmark), 8 h (max. load test) <sup>2)</sup>
Physical Specifications	
<b>Size</b>	203 mm (7.98") x 132 mm (5.20") x 25 mm (0.98"), incl. long life battery
<b>Weight</b>	640 g (1.41 lbs), incl. long life battery
<b>Water</b>	IP65
<b>Altitude</b>	12,192 m (40,000 ft), MIL-STD-810G, Method 500.5, Procedure II
<b>Operating Temperature Range</b>	Specified: -10°C (14°F) to 50°C (122°F) Verified: -29°C (-20°F) to 60°C (140°F), MIL-STD-810G, Method 501.5/502.5, Procedure II
<b>Storage Temperature Range</b>	Specified: -20°C (-4°F) to 60°C (140°F) Verified: -51°C (-60°F) to 71°C (160°F), MIL-STD-810G, Method 501.5/502.5, Procedure I
<b>Humidity</b>	95% RH temp cycle 30°C (86°F)/60°C (140°F) MIL-STD-810G, Method 507.5, Procedure II
<b>Drop</b>	Free to plywood 26 drops from 1.5 m (60") MIL-STD-810G, Method 516.6, Procedure IV.
<b>Vibration</b>	General minimum integrity and helicopter minimum integrity test, MIL-STD-810G, Method 514.6, Procedure I, II;
Accessories	
External 4-bay battery charger, docking station (cradle), 12/24V vehicle charger, additional 7100 mAh battery, pole and vehicle mount solutions, anti-glare screen protectors, hand strap, stylus	

<sup>2)</sup> In continuous field operation mode, may vary with temperature, battery age etc.

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland - Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2015. 836856en-us - 05.15 - INT



**Leica iCON site/iCON build**  
Easy to use construction field software. Designed for construction workers.



**Leica iCON gps 60**  
Versatile SmartAntenna for multipurpose positioning tasks.



**Leica iCON robot 60**  
One-person operation, saving time and increasing productivity when carrying out layout tasks and as-built checks.



**Leica Builder**  
Intuitive, powerful and scalable manual total station series for routine construction tasks on site.



The **Bluetooth®** word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Leica Geosystems AG is under licence. Windows and Windows CE are a registered trademark of Microsoft Corporation. All other trademarks and trade names are those of their respective owners.